

Parts and Service Manuals From:



On Line Materials for the Jan San Industry.

Since 1922

**Michigan Company Inc.
2011 N. High St.
Lansing, Mi 48906
(517) 484-9312**

[Http://www.Michco.Com](http://www.Michco.Com)

Email:Shop@Michco.com

Order parts on line or by Phone

Visa, MasterCard, Amex

Shipping to US addresses only.

Materials contained in this manual Copyright respective manufacturer, PDF version made exclusively by Michco for our customer's use only. Any other use of PDF version violates our PDF copyright.

BR 1000

ORDER #85013

20" 1500 RPM High Speed Burnisher

FEATURES

- Quick Detachable Handle for Easy Transport
- Patented, Infinite Position Handle Height Adjustment
- Super-Flex Switch Levers
- Safety Switch Lock-Out
- Adjustable Dial for Precise Pad Pressure
- Flexible High Speed Pad Holder
- Heavy Duty Transport Wheels
- Direct Drive - No Belts, Gear Box or Pulleys
- Heavy Duty Motor for Durability and Long Life
- 75' Safety Yellow Power Cord


The Betco BR series Burnishers are designed for operator safety and system performance. All BR Burnishers are CSA safety tested and certified. The BR Burnishers are designed with the highest quality components to provide durability, safety and performance.

WARRANTY

3 year (except wear items)*

*Please refer to Betco Equipment Price/Product Guide for complete equipment warranty information.

Authorized Betco Distributor:



SPECIFICATIONS

- Pad Size: 19" or 20"
- Pad Speed: 1500 RPM
- Motor: 1.5hp DC Rectified
- Amp Draw: 14.5 amps
- Cord: 75' Safety Yellow 14/3 Ga.
- Plug: Hospital Approved 3 prong
- Noise Level: 58 dB
- Weight: 76 lbs. (Net)
- CSA Tested and Certified

APPLICATIONS

- Dry Burnishing
- Restorative Burnishing
- Spray Buffing

Better Solutions Come From...

BETCO

1001 Brown Avenue • P.O. Box 3127 • Toledo, Ohio 43607-0127
©All Rights Reserved 5/99 • Reorder #85013



BURNISHER BR 1500

PARTS LIST 85013

ITEM	DESCRIPTION	QTY	ITEM	DESCRIPTION	QTY
85031	TRIGGER ASSEMBLY	1	85090	UHS PAD CENTER LOK	1
85032	MICRO SW 1 1/2 HP	1	85091	WHEEL AXLE PLATED	1
85036	ANTI-KINK SPRING	1	85092	3/8-16 X 5/8 HHCS	4
85038	CORD ASSEMBLY 14/3 X 75'	1	85093	#10-24 X 1/4 SS	8
85041	HANDLE GRIP FOAM	2	85094	5/16-18 X 3/4	1
85042	RECTIFIER	1	85095	FL WASHER 5/16 X 1 X 1/8	1
85043	CASTER UHS B/R SUPPORT	1	85096	SHAFT ADAPTOR PAINTED	2
85044	WEDGE HANDLE	1	85097	UHS BRUSH COVER	1
85045	3/8 LOCKWASHER	4	85098	UHS BRUSH COVER ASS'Y	1
85046	#10-24 X 1/2 PHS	4	85099	UHS BUMPER	1
85047	5/16 FLAT WASHER	4	85100	#6-32 X 7/8 PHS	2
85048	PIGTAIL FEMALE 42 IN.	1	85105	GROMMET 3/8"	1
85049	5/16 SPRING LOCKWASHER	4	85119	HANDLE TUBE	1
85050	1/2 IN. NYLON WASHER	6	85140	#14-1 1/2 TYPE A SCREW	2
85051	1/4-20 X 1-3/4 RHMS	1	85150	#8-32 X 1/2 PHS	4
85052	GROMMET 5/8"	2	85158	1/4-20 X 3/4 HHMS	3
85053	MOTOR CARBON BRUSH	4	85350	1/4-20 X 3/4 RHMS	1
85054	KNOB SAFETY SWITCH	2	85351	HITCH PIN	1
85055	LEVER SAFETY SWITCH	1	85352	UHS HAND WHEEL	1
85056	SPRING SAFETY SWITCH	1	85353	UHS WHEEL STUD	1
85057	#6-32 X 1/4 PHS	2	85354	UHS WHEEL BRACE	1
85058	MAIN FRAME PAINTED	1	85357	MOTOR COVER UHS	1
85059	HANDLE BRACE PAINTED	1	85358	1/4-20 NYLOC NUT	2
85060	AXLE SHAFT PLATED	1	85359	1/2 TENSION WASHER TW8	6
85061	T-HANDLE SUPPORT PAINT	1	85360	SHROUD FILTER SM WET	1
85062	AXLE END CAPS	2	85362	CORD GRIP	2
85063	5/16-18 X 1 1/2 HHMS	4	85363	3/8-16 ACORN NUT FLANGED	1
85064	SWITCH BOX PAINTED	1	85388	HANDLE TUBE PLUG	2
85065	SWITCH BOX COVER PAINT	1	85393	BW 8L BRASS WASHER	1
85066	BRACE LOCK PAINTED	1	85394	#8-32 X 3/4 RHMS	1
85067	HANDLE TUBE PLATED	1	85395	#8-32 NYLOC NUT	1
85068	CAM LEVER ASSEMBLY	1	85396	3/8-16 X 1 HHMS	1
85069	HEYCO CAM LEVER PLUG	1	85397	5/16 X 5/16 SS	1
85070	EXTENSION ROD WELDED	1	85398	#8 X 5/8 PHMS	1
85071	TAPERED SLEEVE	1	85400	UHS SUPPORT WHEEL ASS'Y	1
85072	BUSHING	2			
85073	5/16-18 NYLOC NUT	2			
85074	#6-32 X 3/8" FHS - COVER	4			
85075	FLEXIBLE DRIVE ASS'Y	1			
85080	INDICATOR LIGHT	1			
85082	#8-32 X 1/4 PHS	1			
85083	RESET INSERT	1			
85084	SWITCH INSERT	1			
85086	MOTOR 1-1/2 HP - 1500 RPM	1			
85087	BRACE AXLE PLATED	1			
85088	WHEEL UHS	2			
85089	SUPPORT BRACKET	4			

MAR 98


BURNISHER BR 1500

85013R

ITEM	DESCRIPTION	QTY	ITEM	DESCRIPTION	QTY
85360	SHROUD FILTER SM WET	1	85068	CAM LEVER ASSEMBLY	1
85362	CORD GRIP-STRAIN RELIEF	2	85069	HEYCO CAM LEVER PLUG	1
85363	3/8-16 ACORN NUT FLANGED	1	85070	EXTENSION ROD WELDED	1
04397	UHS CHASSIS PLUG	1	85071	TAPERED SLEEVE	1
04905	1/4-20 X 3/4" PHS	2	85072	BUSHING	2
04906	1/4" LG DIA. WASHER	2	85073	5/16-18 NYLOC NUT	2
04909	TRIGGER TX	1	85074	8-32 X 1/4 C'SUNK SCREW	4
04910	LEVER SAFETY SWITCH TX	1	85075	FLEXIBLE DRIVE ASSEMBLY	1
04912	UHS ADJUST KNOB	1	85082	8-32 X 1/4 TAPTITE PHILLIPS	1
04914	BRACE AXLE PLATED	1	85084	SWITCH INSERT	1
04916	WHEEL AXLE PLATED	1	85086	MOTOR UHS 1500 RPM	1
04922	UHS BUMPER	1	85089	SUPPORT BRACKET	4
04923	UHS WHEEL STUD	1	85090	UHS PAD CENTRE LOK	1
04927	CHASSIS-POLY UHS	1	85092	3/8-16 X 5/8 HHCS	4
04965	MOTOR COVER UHS TX	1	85093	10-24 X 1/4 SS	1
85032	MICRO SW 1 1/2 HP	1	85094	5/16-18 SHCS	1
85036	ANTI-KINK SPRING	1	85095	CUP WASHER	1
85038	14/3 X 75 FT CORD SET	1	85100	6-32 X 7/8 TAPTITE PHILIPS	2
85041	HANDLE GRIP FOAM	2	85105	GROMMET 3/8"	1
85042	RECTIFIER	1	85119	HANDLE TUBE	1
85043	CASTER UHS B/R SUPPORT	1	85140	#14-1 1/2 TYPE A SCREW	2
85044	WEDGE HANDLE	1	85144	INDICATOR LIGHT	1
85045	3/8 SPRING LOCK WASHER	4	85150	8-32 X 1/2 TAPTITE PHILLIPS	4
85046	10-24 X 1/2 PHS PHILLIPS	2	85158	1/4-20 X 3/4 HHCS	3
85047	5/16 FLAT WASHER	4	85351	HITCH PIN	1
85048	PIGTAIL FEMALE 42 IN.	1	85358	1/4-20 NYLOC NUT	2
85049	5/16 SPRING LOCKWASHER	4	85359	1/2 TENSION WASHER TW8	2
85050	1/2 IN. NYLON WASHER	4	85380	10-24 X 3/4 PHS PHILLIPS	1
85053	MOTOR BRUSH	4	85383	WHEEL 5in FLOOR MACH	2
85054	KNOB SAFETY SWITCH	2	85388	HANDLE TUBE PLUG	2
85056	SPRING SAFETY SWITCH	1	85397	5/16-18 X 5/16 SET SCREW	1
85057	6-32 X 1/4 TAP SCREW	2	85398	#8 X 5/8 PHSMS	3
85059	HANDLE BRACE PAINTED	1			
85060	AXLE SHAFT PLATED	1			
85061	T-HANDLE SUPPORT PAINT	1			
85062	AXLE END CAPS	2			
85063	5/16-18 X 1 1/2 HBB	4			
85064	SWITCH BOX	1			
85065	SW/ BOX COVER	1			
85066	BRACE LOCK PAINTED	1			
85067	HANDLE TUBE PLATED	1			

SEP 98

07547





Operator Manual - BURNISHERS DUST 2000/2500 BR1500/2000 BR750/1500

INTRODUCTION

This manual will help you get the most from your Betco Burnisher. Read it thoroughly before operating.

The Betco Burnisher is intended for commercial use.

PARTS & SERVICE:

Contact your BETCO AUTHORIZED DISTRIBUTOR for repair parts or service. Please specify the Model & Serial Number when discussing your machine.

NAME PLATE:

The Model & Serial Number of your machine is located on the Name Plate on the back of the handle assembly. This information is often needed when ordering repair parts for the machine.

IMPORTANT SAFETY INSTRUCTIONS

When using an electrical appliance, basic precautions should always be followed, including the following:
Read all instructions before using.

! WARNING !

To reduce risk of fire, electric shock, or injury:

- * Do not leave the machine when it is plugged in. Unplug the unit from the outlet when not in use & before servicing.
- * To avoid electric shock, do not expose machine to rain. Store indoors.
- * Do not allow to be used as a toy. Close attention is necessary when used by or near children.
- * Use only as described in this manual. Use only manufacturer's recommended attachments.
- * Do not use with damaged cord or plug. If machine is not working as it should return it to a service center for inspection.
- * Do not pull or carry by cord, use cord as a handle, close a door on a cord, or pull cord around sharp edges or corners. Do not run machine over cord. Keep cord away from heated surfaces.
- * Do not unplug by pulling on cord. To unplug, grasp the plug, not the cord.
- * Do not handle plug or machine with wet hands.
- * Do not put any foreign object into openings. Do not use with any opening blocked; keep free of dust, lint, hair, & anything that may reduce air flow.
- * Keep hair, loose clothing, fingers, & all parts of body away from openings & moving parts.
- * Turn off all controls before unplugging.
- * Do not use in or around flammable or combustible liquids such as gasoline or use in areas where they may be present.
- * Connect to a properly grounded outlet only. See grounding instructions.

GROUNDING INSTRUCTIONS

This machine must be grounded. If it should electrically malfunction, grounding provides a path of least resistance for electric current to reduce the risk of electric shock. This machine is equipped with a cord having an equipment-grounding conductor & grounding plug. The plug must be plugged into an appropriate outlet that is properly installed & grounded in accordance with all local codes & ordinances.

! DANGER !

Improper connection of the equipment-grounding conductor can result in a risk of electric shock. Check with a qualified electrician or service person if you are in doubt as to whether the outlet is properly grounded. Do not modify the plug provided with the machine. If plug will not fit the outlet, have a proper outlet installed by a qualified electrician.

Replace the plug if the grounding pin is damaged or broken.

Extension cords connected to this machine should be 12 gauge, 3-wire cords with 3-prong plugs & outlets. DO NOT use extension cords more than 50 feet long.

PREPARING THE MACHINE FOR OPERATION

! WARNING !

This machine contains moving parts. To reduce the risk of injury, always unplug the power cord before servicing.

With the handle locked in the upright position, tip the entire machine backward, resting on handle assembly.

Align the proper burnishing pad on the flex-drive pad drive assembly, secure with locking plate, hand tight only.

! CAUTION !

Using the wrong pad on this machine can damage the floor or overload the motor. Before using, always make sure floor is clean & dry.

Unwrap the power cord completely & plug into a properly grounded outlet.

Adjust the handle to a comfortable position. This adjustment will vary from operator to operator.

Adjust the burnishing head for proper pad pressure using the adjustment knob located on the front of the burnisher.

Be prepared to control the machine as soon as you release the safety lock tab & pull either switch lever.

Immediately start moving forward. Keep the machine moving while the motor is running.

Note: When the dual controlled switch levers are released, the machine shuts off immediately.

SPRAY BURNISHING BR1500 BR2000 BR750/1500

Lightly spray floor area to be burnished. (3 or 4 passes will restore appearance level)

RESTORER BURNISHING Dust 2000 Dust 2500

Lightly mop floor with properly diluted restorer. Allow to dry before burnishing. Each side of a burnishing pad will cover approximately 500 square feet. Floors will require scrubbing & recoating periodically depending on wear & use.

Note: Dust Control Models Should Not Be Used For Spray Buffing. Spray Buffing Will Clog Filter And Damage Dust Control Skirt.

AFTER USE

Return handle assembly to the upright, locked position.

Unplug the power cord, starting from the machine wrap the power cord onto the handle assembly.

With the machine in the upright, locked position, tip the entire machine backward, resting on the handle assembly.

Remove the burnishing pad from the machine. (clean all burnishing pads)

Wipe the entire machine with a clean, damp cloth.

Inspect the machine & all accessories for damage. Perform any required maintenance or repairs before storage.

Store the machine in a clean, dry place with the handle in the upright, locked position resting on pad.



Thank you for choosing

Floor Care Equipment!