



2000 sq.ft./gallon

FINISH 101™



Acrylic Polymer Floor Finish

This finish delivers both optimal value and performance, and is developed specifically for facilities that desire to contain floor maintenance costs. Educational facilities, contractors and retail facilities will realize savings to their bottom line, while also meeting bid specifications. We have utilized a unique polymer formulation to obtain higher cross linked density resulting in lasting durability. This formula is designed for low maintenance programs where burnishing is minimal or unavailable. Great off the mop gloss, quick build and superior leveling make this finish easy to apply by any personnel.

Uses

- Resilient tile
- Terrazzo

Features

- Reduced labor - Fast build with fewer coats.
- Optimal value and performance.
- Durable with higher cross link density.
- Deep gloss.
- Clear, bright appearance - Non-yellowing polymer formula.
- Self-leveling, self-sealing.
- Scuff resistant.

Properties

Color (dried).....	Crystal clear
Color (liquid)	White
Coverage.....	2,000 square feet/gallon
Dry time.....	20 - 30 minutes
Fragrance.....	Mild
Freeze/thaw stability	3 cycles
Gloss (ASTM D 1455-87).....	One coat 75 - 80 Two coats 80 - 85
Heel mark resistance	Excellent
Leveling	Excellent
pH.....	8.1 - 8.9
Powdering resistance	Excellent
Recoat	Excellent
Specific gravity	1.03
Free styrene content.....	0.0
Shelf life.....	1 year

Directions For Use

Read the entire label before using this product.

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces. **RESTORATIVE MAINTENANCE:** Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. Elevated temperatures and humidity may extend dry time. 4 - 5 coats of finish are recommended. **Note: This product is a self sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of a sealer will enhance gloss and long term performance.** **ROUTINE MAINTENANCE:** Sweep large debris and dust mop (using a water based treatment). Damp mop or automatic scrub using a neutral pH cleaner. Buff or burnish the floor as desired. The use of a cleaner/restorer is recommended to condition the floor and extend the time between top scrub and recoating. **INTERIM MAINTENANCE:** Sweep large debris and dust mop (using a water-based treatment). Top scrub the floor using a top scrub cleaner and recommended floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above. **Note: Slip resistance meets or exceeds standard, (ASTM D 2047-04) James Machine 0.5 minimum.**

Safety

Keep out of reach of children. For institutional and commercial use. **CAUTION:** Contains glycol ethers. Avoid contact with skin and eyes. Harmful if swallowed. **FIRST AID:** If splashed on skin or in eyes, flush with large quantities of water. If swallowed, drink two glasses of water. Call a physician.

Available In

Case/4 - 1 Gallon (3.78 L): Item #69604-00
Pail/5 Gallon (18.9 L): Item #69605-00
Drum/55 Gallon (208 L): Item #69655-00

Literature Item #69692-92

