



2000 - 3000 sq.ft./gallon

UNTOUCHABLE®

with **SRT™**
SCUFF RESISTANT TECHNOLOGY



Metal Interlocked Floor Finish and Basecoat

Betco's Untouchable® with Scuff Resistant Technology™ (SRT) is a low odor, black heel mark resistant floor finish that is an exceptional choice for those who want the highest gloss and wear with the least amount of labor. Untouchable with SRT is non-scuffing, durable, detergent resistant and maintains its high gloss with minimal burnishing, a real labor saver. Suitable for use on all floors; this finish performs exceptionally well with either spray buffing or high speed buffing. Excellent leveling and low odor makes it easy to apply.

Uses

- Resilient flooring
- Terrazzo

Features

- Superior Black Heel Mark Resistance – Minimizes the need to remove scuff marks
- Extremely Low Odor – Pleasant to use
- Eliminates the need for aggressive cleaning pads – Extends the life of the floor
- Durable – Superior protection for your floor
- Ease of use – Self-leveling, excellent flow for easy application with little or no mop drag
- Self-sealing – Reduces cost
- Versatile – For use on all resilient flooring as well as terrazzo

Properties

Coverage.....	2,000 - 3,000 sq. ft./gal.
Drying time.....	20 - 30 minutes
Fragrance.....	Mild
Freeze/thaw stability.....	3 cycles
Gloss (ASTM D 1455-87)	One coat 80 - 85 Two coats 97 - 98
Heel mark resistance	Excellent
Leveling	Excellent
pH.....	8.1 - 8.9
Powdering resistance	Excellent
Recoat	Very good
Specific gravity	1.03
Free styrene content.....	0.0
Shelf life.....	1 year

KEEP FROM FREEZING

Directions For Use

Read the entire label before using this product.

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces. RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. Elevated temperatures and humidity may extend dry time. 4 - 5 coats of finish are recommended. **Note: This product is a self sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of a sealer will enhance gloss and long term performance.** ROUTINE MAINTENANCE: Sweep large debris and dust mop (using a water based treatment). Damp mop or automatic scrub using a neutral pH cleaner. Buff or burnish the floor as desired. The use of a cleaner/restorer is recommended to condition the floor and extend the time between top scrub and recoating. INTERIM MAINTENANCE: Sweep large debris and dust mop (using a water-based treatment). Top scrub the floor using a top scrub cleaner and recommended floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above. **Note: Slip resistance meets or exceeds standard, (ASTM D 2047-04) James Machine 0.5 minimum.**

Safety

Keep out of reach of children. For institutional and commercial use. **WARNING:** MAY CAUSE EYE IRRITATION. Contains glycol ether. Avoid contact with skin and eyes. Harmful if swallowed. **FIRST AID:** If splashed on skin or in eyes, flush with large quantities of water. Seek medical attention if irritation persists. If swallowed, drink two glasses of water. Call a physician.

Available In

Case/4 - 1 Gallon (3.78 L): Item #60604-00
Box/2-1.125 Gallon Bags (4.25 L): Item #60659-00 (QUICKCOAT®)
BIB/5 Gallons (18.9 L): Item #60639-00
Pail/5 Gallon (18.9 L): Item #60605-00
Drum/55 Gallon (208 L): Item #60655-00

